

Enhanced Megapixel IP Camera **PUSH Video, FocusAssist, Wi-Fi & POS...**



KC-IV321L

2 M/P Full HD (1080p) Vandal Dome IP Camera

- 2 M/P 16:9 Full HD Resolution (30 fps@1080p)
- 1/3" Panasonic Progressive Scan CMOS
- Built-In ICR Filter for Day & Night Operation
- IEEE 802.3af Compliant PoE
- FocusAssist for Easy Focus Control, WDR, Defog

- ✓ H.264 Dual-Stream with Adjustable fps & Resolution
- ✓ PUSH Video Call to iPhone & iPad for Instant Monitoring
- ✓ Compatible with ONVIF v2.2
- ✓ Wi-Fi Transmission by USB Wi-Fi Module
- ✓ POS Function by USB-to-RS232 Converter
- ✓ Local Recording by Micro SD Card (Continuous, Event & Network-Failed Mode)
- ✓ Integrated Network Solution by CMS & Mobile-Viewer & Web-Viewer
- ✓ 64 Ch NVR Software Included as Default Package



KC-IV321L

2 M/P Vandal Dome IP Camera

Integrated Network Software

- CMS
- Web-Viewer
- Mobile-Viewer
- 64 Ch NVR Software



CMS




WEB VIEWER



Mobile Viewer

Dimension

(Unit : mm)



Related Products



Specification


ONVIF v2.2

Model	KC-IV321L	KC-IV321LH
Video		
Image Sensor	1/3" Panasonic Progressive CMOS	
Max. Resolution	1920 x 1080	
Min. Illustration	Color : 1.0 Lux, 0.002 Lux (Sens-up) BW : 0.5 Lux, 0.001 Lux (Sens-up)	
Video Out	CVBS : 1.0 Vp-p/75 ohm Composite	
Lens		
Lens Type	DC Auto Iris	
Mount Type	Board-in Type	
Focal Length	f : 2.8~12 mm	
Aperture Ratio	F1.4	
View Angle (H & V)	H : 92°~ 27.2°, V : 69°~ 20.4°	
Pan/Tilt/Rotate	0°~355° / 0°~90° / 0°~355°	
Focus Control	Manual & FocusAssist	
Operation		
ICR for Day & Night	Yes	
IR LED	30 pcs	
Night Vision Distance	25 meters	
OSD Control	Through Web	
ID & Camera Title	On / Off	
Day & Night	Auto(ICR) / Color / BW / EXT_L / EXT-H	
BLC/WDR	Off / WDR / BLC / Defog / HLC	
3D-DNR	Off / Low / Middle / High	
Motion Detection	16 Blocks (On / Off)	
Privacy Masking	16 Masks (On / Off)	
Digital Zoom	x1~x4 (On / Off)	
Electronic Shutter Speed	Auto / Manual (1/50~1/60,000 Sec) / FLK	
Sens-Up (Digital Slow Shutter)	Off / x2 ~ x8	
AGC	On / Off (0~20 Steps)	
White Balance	Auto / Autoext / Push / Manual	
Flip/Mirror	Flip On / Off, Mirror On / Off	
Alarm I/O	1 / 1	
Alarm Event	Event Recording on Micro SD Card, E-Mail Notification with Snap Shot File Upload via FTP Server	
RS-485	Yes	
Network		
Ethernet	RJ-45 (10/100 Base-T)	
Connection Mode	Fixed IP, DHCP & DDNS	
Video Compression	H.264	
Frame & Resolution	Max. 30 fps at 1920x1080	
Dual-Stream	Main Stream(1080p) & Sub-Stream(D1)	
Bitrate Control	CBR/VBR, Network Bandwidth Control	
Audio I/O	Line-in / Line-out	
2-Way Audio	Yes	
Protocol	TCP/IP, HTTP, RTP/RTSP, UDP, DHCP, FTP, SMTP, NTP, ARP, ICMP, DDNS(STL), ONVIF(v2.2), STL	
Security	Multi-Level Passwod, IP&Mac Filtering	
Max. User Access	Up to 32	
ONVIF Compliance	v2.2	
Remote Monitoring	CMS & MobileViewer (iPhone & Android Phone) All Kinds of Web Browser (I/E, Safari, Chrome,Firefox, Opera)	
Record		
Local Record	Micro SD/SDHC Card (with Safety Removal)	
Remote Record	64 Ch NVR S/W (Default Package)	
Local Record Mode	Continuous, Motion, Sensor Recording & NFR (Network Failed Recording)	
Special Features		
PUSH Video Call	PUSH Video Call to iPhone/iPad	
Wireless (Wi-Fi)	Option (USB Wi-Fi Module)	
POS Integration	Option (USB-to-RS232 Converter)	
Intensive Record	Yes	
Environment		
Installation	Outdoor	
Weather Proof	IP66	
Vandal Proof	Yes	
Operating Temp/Humidity	-10 ~ 55 °C / Less than 90% RH	-40 ~ 55 °C with Fan&Heater
Built-in Fan & Heater	--	Heater works at A/C 24V
General		
Input Voltage	D/C12V & A/C24V and PoE (IEEE 802.3 af)	
Dimension	150 x 127 mm (DxH)	

(*) Design and specification are subject to change without prior notice.



Distributed By



Hong Kong (Head Quarter)

STL Security Limited

Flat A, 9/F., Wing Cheung Ind. Bldg.,
58-70 Kwai Cheong Rd, Kwai Chung,
Hong Kong

Tel: (852) 2805-1298
Inquiry: sales1@stl-cctv.com

Korea (R&D Center)

MCC System Co., Ltd.

#410, Woolim Lions Valley 2-cha,
680 Gasan-dong, Geumcheon-gu,
Seoul, Korea 153-776

Tel: (82) 2-2027-2590
Inquiry: sales2@stl-cctv.com

China (Main Factory)

STL Security (Shenzhen) Limited

2/F West, Block 2, Shunheda Factory
Area, Liuxiandong Industrial Zone, Xili
Nanshan District, Shenzhen, China.

Tel: (86) 755 2592 0069
Inquiry: sales3@stl-cctv.com